Brancoforte Paints

BRANCO FORTE Paints

PRIMER PARA MADEIRA FEITO PARA ADERIR ZARCAO

WOOD PRIMER

BUILT TO BOND

PRIMER THAT LOCKS IN THE PAINT FILM

Primer que fixa a película de tinta







Diluível em Solvente

Fabricado na Índia

Made in India

BRANCO FORTE

Paints

Brancoforte Paints – Primário para Madeira

FEITO PARA ADERIR
Primário que fixa a película de tinta

Descrição do Produto:
O Primário para Madeira Brancoforte Paints é uma subcamada de qualidade premium, concebida para proporcionar aderência excecional e proteção duradoura em todos os tipos de superfícies de madeira. Penetra profundamente para selar o veio da madeira e cria uma forte camada de ligação que melhora a durabilidade e o acabamento da demão final.

Características Principais:

Tecnologia de Aderência Reforçada
Fixa firmemente a película de tinta à madeira, para maior durabilidade.

Adequado para Uso Exterior e Interior
Oferece um desempenho fiável em aplicações tanto no exterior como no interior.

Sela e Protege a Superfície da Madeira
Impede a penetração de humidade e resiste ao empolamento e ao descasque.

Base Lisa para Pintura
Cria uma superfície uniforme, melhorando o aspeto e a duração da tinta.

Utilização Recomendada:
Ideal para portas, janelas, mobiliário, painéis e todos os trabalhos em madeira que exijam uma base de primário robusta e duradoura.

Método de Aplicação:
Pincel, rolo ou pistola. Certifique-se de que a superfície está limpa, seca e lixada antes da aplicação. Mexa bem antes de usar. Diluição: 10–15% de aguarrás mineral. Rendimento: aprox. 10–12 m²/L por demão. Aplique 1 demão de primário e 2 de acabamento.

Tempo de Secagem:

Seco ao toque:
30 minutos

Nova demão:
4–6 horas

Acabamento:
Acabamento mate, para proporcionar excelente aderência às demãos finais.

Brancoforte Paints – Wood Primer

BUILT TO BOND
Primer That Locks in the Paint Film

Product Description:
Brancoforte Paints Wood Primer is a premium quality undercoat designed to deliver exceptional adhesion and long-lasting protection for all types of wooden surfaces. It penetrates deeply to seal the wood grain and creates a strong bonding layer that enhances topcoat durability and finish.

Key Features:

Enhanced Adhesion Technology
Locks the paint film firmly to the wood for superior durability.

Suitable for Exterior & Interior Use
Offers reliable performance in both outdoor and indoor applications.

Seals & Protects Wood Surface
Prevents moisture penetration and resists blistering or peeling.

Smooth Base for Painting
Creates an even surface, improving paint appearance and lifespan.

Recommended Use:
Ideal for wooden doors, windows, furniture, panels, and all woodwork requiring a robust and lasting primer base.

Application Method:
Brush, roller, or spray. Ensure the surface is clean, dry, and sanded before application. Stir well before use. Dilution: 10–15% mineral turpentine oil. Coverage: approx. 10–12 m²/L per coat. Apply 1 coat of primer and 2 topcoats.

Drying Time:

Touch dry:
30 minutes

Recoat:
4–6 hours

Finish:
Matt finish to provide excellent grip to topcoats.

☐ 1L ☐ 4L



FLAMABLE LIQUID 1

Validade: 18 meses a partir da data de embalagem.
Best before 18 months from date of packing.

Exported by:
NOWPUREIT

Web: www.brancoforte.com
E-mail: admin@brancoforte.com

Peso líquido / NETT:

Preço máx. / PVP / MRP:

USP:

Lote / BATCH CODE:

Embalado em / PACKED ON: